



# TECHNICAL DATA SHEET **LED NGP**





### **LED-NGP-11** X-RAY FILM VIEWER

#### **HOW DOES THE X-RAY FILM VIEWER WORK?**

LED-NGP X-ray film viewers are medical devices designed for the analysis of medical images on X-ray films, which is one of the basic methods of diagnosing human diseases. X-ray film viewers manufactured in LED technology have extremely efficient parameters, such as the value of luminance intensity, uniformity of screen luminance, low operating cost-long lifetime, and low energy consumption. The devices do not come into contact with patients as they are devices supporting the process of analyzing X-rays by a doctor. The products are made in the 1st class of protection against electric shock. They can be used in operating theaters, doctor's offices, X-ray laboratories, etc.

#### **BASIC DATA:**

Mounting type	table top stand / wall- mounted
Casing material	powder-coated steel sheet
Viewer screen material	PMMA
Switch on/off	built-in x-ray film viewer body (Fig. 1 point 2)
Automatic clip for X-ray film	yes
Ambient temperature	+10°C to +40°C
Relative humidity	30% to 70%
Atmospheric pressure	700 hPa to 1060 hPa
Declaration of conformity	yes
User's manual English version	yes







"Knob" for a smooth luminance adjustment with ON/OFF screen backlight

EDITION: 10/2022





#### **TECHNICAL DATA SHEET**

### **LED NGP**

## **LED-NGP-11** X-RAY FILM VIEWER

#### **TECHNICAL DATA:**

Power cord length

Supply voltage	90-260 V, 50-60 Hz
Power consumption	65 W
Luminance	600-6000 cd/m² +/- 15 % (19 000 lux)
Light uniformity	≥95 %
Step-less luminance adjustment (each frame separately)	10 - 100 %
Colour temperature of the light of the lamps	> 6500 °K
Lifetime span	50 000 working hours (average 25 years)
Absolutely no light flickering	yes
Screen dimensions (L x H)	36 x 43 cm
Overall dimensions (L x W x H)	430 x 35 (+15 knob) x 520 mm
Total mass	4.5 kg
Class of protection against electric shock	I
Ingress Protection Code	IP 20
Class for the medical environment	B - home
Group according to PN-EN 55011 Clause 5	1




Fig.1. X - Ray film viewer LED-NGP-11

- 1. connection unit with fuses
- 2. main switch
- 3. luminance adjustment knob with a switch off/ on
- 4. screen
- 5. film holder
- 6. switch off the "glare"
- 6\*. for LED-NGP 31 and LED-NGP 41 X-ray viewers switch off the "glare" is near the luminance adjustment knob on the front panel

2.5 m, ended with the socket plug