



Ultra-Viol sp.j. Pietras, Purgał, Wójcik Stępowizna 34, 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en

Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET





LED-NGP-31WS

X-RAY FILM VIEWER

HOW DOES THE X-RAY FILM VIEWER WORK?

LED-NGP X-ray film viewers are medical devices designed for the analysis of medical images on X-ray films, which is one of the basic methods of diagnosing human diseases. X-ray film viewers manufactured in LED technology have extremely efficient parameters, such as: value of luminance intesity, uniformity of screen luminance, low operating cost-long lifetime, low energy consumption. The devices do not come into contact with patients as they are devices supporting the process of analyzing X-rays by a doctor. The products are made in the 1st class of protection against electric shock. They can be used in operating theaters, doctor's offices, X-ray laboratories, etc.

BASIC DATA:

Mounting type	recessed into the wall
Casing material	powder-coated steel sheet
Viewer screen material	PMMA
Front panel material	acid-proof steel
Switch on/off	in a knob (front panel)
Automatic clip for X-ray film	yes
Ambient temperature	+10°C to +40°C
Relative humidity	30% to 70%
Atmospheric pressure	700 hPa to 1060 hPa
Declaration of conformity	yes
User's manual English version	yes





Ultra-Viol sp.j. Pietras, Purgał, Wójcik Stępowizna 34, 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en

Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET



LED-NGP-31 WS

X-RAY FILM VIEWER

TECHNICAL DATA:	
Supply voltage	90-260 V, 50-60 Hz
Power consumption	180 W
Luminance	600-6000 cd/m ² +/- 15 % (19 000 lux)
Light uniformity	≥90 %
Step-less luminance adjustment (each frame separately)	10 - 100 %
Colour temperature of the lamps light	> 6500 °K
Life-time span	50 000 working hours (average 25 years)
Absolutely no light flickering	yes
Screen dimensions (L x H)	108 x 43 cm
Recess dimensions (L x W x H)	1155 x 50 x 545 mm
Overall dimensions (L \times W \times H)	1190 x 74 x 580 mm
Total mass	13.8 kg
Class of protection against electric shock	I
Ingress Protection Code	IP 20
Class for the medical environment	B - home
Group according to PN-EN 55011 Clause 5	1
Power cord length	0.2 m

Front panel F

LED-NGP WS X-ray film viewer

Fig. 2 View of the LED-NGP WS after the installation



Ultra-Viol's realisation