

LED-NGP-41 X-RAY FILM VIEWER

HOW DOES THE X-RAY FILM VIEWER WORK?

LED-NGP X-ray film viewers are medical devices designed for the analysis of medical images on X-ray films, which is one of the basic methods of diagnosing human diseases. X-ray film viewers manufactured in LED technology have extremely efficient parameters, such as: value of luminance intesity, uniformity of screen luminance, low operating cost-long lifetime, low energy consumption. The devices do not come into contact with patients as they are devices supporting the process of analyzing X-rays by a doctor. The products are made in the 1st class of protection against electric shock. They can be used in operating theaters, doctor's offices, X-ray laboratories, etc.

BASIC DATA:

table top stand / wall- mounted Mounting type Casing material powder-coated steel sheet Viewer screen material **PMMA** Switch on/off built in x-ray film viewer body (Fig. 1 point 2) Automatic clip for X-ray film yes Ambient temperature +10°C to +40°C 30% to 70% Relative humidity 700 hPa to 1060 hPa Atmospheric pressure Declaration of conformity yes User's manual English version yes







"Knob" for a smooth luminance adjustment with ON/OFF screen backlight






TECHNICAL DATA SHEET

LED NGP

LED-NGP-41 X-RAY FILM VIEWER

TECHNICAL DATA:

TECHNICAL DATA.	
Supply voltage	90-260 V, 50-60 Hz
Power consumption	250 W
Luminance	600-6000 cd/m² +/- 15 % (19 000 lux)
Light uniformity	≥95 %
Step-less luminance adjustment (each frame separately)	10 - 100 %
Colour temperature of the lamps light	> 6500 °K
Life-time span	50 000 working hours (average 25 years)
Absolutely no light flickering	yes
Screen dimensions (L x H)	144 x 43 cm
Overall dimensions (L x W x H)	1520 x 35 (+15 knob) x 520 mm
Total mass	16.0 kg
Class of protection against electric shock	I
Ingress Protection Code	IP 20
Class for the medical environment	B - home
Group according to PN-EN 55011 Clause 5	1



Power cord length

Fig.1. X - Ray film viewer LED-NGP-11

- 1. connection unit with fuses
- 2. main switch
- 3. luminance adjustment knob with a switch off/ on
- 4. screen
- 5. film holder
- 6. switch off the "glare"
- 6*. for LED-NGP 31 and LED-NGP 41 X-ray viewers switch off the "glare" is near the luminance adjustment knob on the front panel

2.5 m, ended with the socket plug