




TECHNICAL DATA SHEET







DIRECT RADIATION UV-C GERMICIDAL LAMP FOR INDUSTRIAL USE

HOW DOES THE DIRECT RADIATION UV-C GERMICIDAL LAMP FOR INDUSTRIAL USE WORK?

Direct radiation germicidal lamps type NBV IP65 are designed to prevent primary and secondary infections in the food, pharmaceutical and cosmetic industries, warehouses, and everywhere the production process takes place. Direct radiation germicidal lamps applied in the rooms where airborne pathogenic microorganisms (pathogens) live, significantly reduce the probability of spreading the infection by air. Raising the level of microbiological purity of the air and surface helps to destroy and reduce the impact of existing outbreaks of pathogens.



BASIC DATA:

| BASIC DATA: | |
|---|---|
| Airflow disinfection function (flow disinfection chamber) | no |
| Direct radiation function | yes |
| Presence of people, animals, plants inside the room during the disinfection process | not allowed |
| Mounting type | on mobile stand (additional charge) |
| Working time counter | no |
| External bulbs | yes, 2 bulbs (covered with anti-splashing foil) |
| Casing material | powder lacquered aluminum |
| Reflector material | steel |
| Switch on/off | built-in lamp body |
| Ambient temperature | +10°C to +40°C |
| Relative humidity | 30% to 70% |
| Atmospheric pressure | 700 hPa to 1060 hPa |
| Declaration of conformity | yes |
| User's manual English version | yes |





TECHNICAL DATA SHEET

NBV IP65 series

NBV 2x15 IP65 P

DIRECT RADIATION UV-C GERMICIDAL LAMP FOR INDUSTRIAL USE

TECHNICAL DATA:

| TECHNICAE DATA. | |
|---|---------------------------------|
| Supply voltage | 230 V, 50 Hz |
| Power consumption | 40 W |
| UV-C bulbs (Philips/Osram) | 2 x 15 W (TUV/HNS) |
| UV-C radiation wavelength | 253.7 nm |
| The useful lifetime of the UV-C bulbs | min. 9000 h |
| The radiation intensity of the external UV-C tube at a distance of 1m | 1 W/m ² |
| The effective area of the lamp | spotwise |
| Class of protection against electric shock | I |
| Ingress Protection Code | IP 65 |
| Lamp body dimensions (L x W x H) | 210 x 160 x 525 mm |
| Overall dimensions (L x W x H) | 600 x 600 x 1210 mm |
| Lamp body mass | 2.0 kg |
| Total lamp mass | 5.6 kg |
| Stand length | 117 cm |
| Power cord length | 3 m, ended with the socket plug |

APPLICATION RECOMMENDATIONS:

Pharmaceutical industry Food industry Cosmetic industry Warehouses Industrial kitchens



Anti-splashing foil protection



Ultra-Viol's realisation