



Ultra-Viol sp.j. Pietras, Purgał, Wójcik 34 Stępowizna Str., 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET NBV IP65 series

DIRECTRADIATION

CLEAN AIR AND SURFACE

NBV 2x36 IP65 P

DIRECT RADIATION UV-C GERMICIDAL LAMP FOR INDUSTRIAL USE

HOW DOES THE DIRECT RADIATION UV-C GERMICIDAL LAMP FOR INDUSTRIAL USE WORK?

Direct radiation germicidal lamps type NBV IP65 are designed to prevent primary and secondary infections in the food, pharmaceutical and cosmetic industries, warehouses, and everywhere the production process takes place. Direct radiation germicidal lamps applied in the rooms where airborne pathogenic microorganisms (pathogens) live, significantly reduce the probability of spreading the infection by air. Raising the level of microbiological purity of the air and surface helps to destroy and reduce the impact of existing outbreaks of pathogens.



BASIC DATA:

Airflow disinfection function (flow disinfection chamber)	no
Direct radiation function	yes
Presence of people, animals, plants inside the room during the disinfection process	not allowed
Mounting type	on mobile stand (additional charge)
Working time counter	no
External bulbs	yes, 2 bulbs (covered with anti-splashing foil)
Casing material	powder lacquered aluminum
Reflector material	steel
Switch on/off	built-in lamp body
Ambient temperature	+10°C to +40°C
Relative humidity	30% to 70%
Atmospheric pressure	700 hPa to 1060 hPa
Declaration of conformity	yes
User's manual English version	yes





Ultra-Viol sp.j. Pietras, Purgał, Wójcik 34 Stępowizna Str., 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en

Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET

NBV IP65 series

NBV 2x36 IP65 P

DIRECT RADIATION UV-C GERMICIDAL LAMP FOR INDUSTRIAL USE

TECHNICAL DATA:

Supply voltage	230 V, 50 Hz
Power consumption	75 W
UV-C bulbs (Philips/Osram)	2 x 36 W (TUV/HNS)
UV-C radiation wavelength	253.7 nm
The useful lifetime of the UV-C bulbs	min. 9000 h
The radiation intensity of the external UV-C tube at a distance of 1m	2.8 W/m ²
The effective area of the lamp	20-25 m ²
Class of protection against electric shock	I
Ingress Protection Code	IP 65
Lamp body dimensions (L x W x H)	210 x 160 x 1285 mm
Overall dimensions (L x W x H)	600 x 600 x 1490 mm
Lamp body mass	4.2 kg
Total lamp mass	7.8 kg
Stand length	117 cm
Power cord length	3 m, ended with the socket plug

APPLICATION RECOMMENDATIONS:

Pharmaceutical industry Food industry Cosmetic industry Warehouses Industrial kitchens



Anti-splashing foil protection



Ultra-Viol's realisation