



Ultra-Viol sp.j. Pietras, Purgał, Wójcik 34 Stępowizna Str., 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET



NGP 21 mZ X-RAY FILM VIEWER WITH SHUTTERS FOR MAMMOGRAMS

HOW DOES THE X-RAY FILM VIEWER FOR MAMMOGRAMS WORK?

NGP mZ/mZU X-ray film viewers with shutters are medical devices designed for the analysis of medical mammography images on X-ray films, which is one of the basic methods of diagnosing human diseases. The devices are characterized by high luminous flux density, flicker-free, energy-saving highfrequency light for film reading without eyestrain. The devices do not come into contact with patients as they are devices supporting the process of analyzing X-rays by a doctor. The products are made in the 1st class of protection against electric shock. They can be used in operating theaters, doctor's offices, X-ray laboratories, etc.



Shutter repositioning handle

BASIC DATA:	
Mounting type	wall-mounted
Casing material (viewer housing)	powder-coated steel sheet
Viewer screen material	PMMA
Switch on/off	built-in x-ray film viewer body (Fig. 1 point 1)
X-ray viewer supplied with a magnifying glass	yes
Ambient temperature	+10°C to +40°C
Relative humidity	30% to 70%
Atmospheric pressure	700 hPa to 1060 hPa
Declaration of conformity	yes
User's manual English version	yes





Ultra-Viol sp.j. Pietras, Purgał, Wójcik 34 Stępowizna Str., 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

TECHNICAL DATA SHEET

NGP mZ/mzU

NGP 21 mZ

X-RAY FILM VIEWER WITH SHUTTERS FOR MAMMOGRAMS

TECHNICAL DATA:

Supply voltage	230 V, 50 Hz
Power consumption	100 W
Luminance	6800 cd/m ² +/- 10 %
Light uniformity	≥90 %
Step-less luminance adjustment	10 - 100 %
Colour temperature of the light of the lamps	≈ 6500°K (daylight)
Shutters for glare-free reading of radiographs	yes
Screen dimensions (L x H)	36 x 46 cm
Overall dimensions (L x W x H)	680 x 120 x 720 mm
Total mass	24.0 kg
Class of protection against electric shock	I
Ingress Protection Code	IP 20
Class for the medical environment	B - home
Group according to PN-EN 55011 Clause 5	1
Power cord length	2.5 m, ended with the socket plug




Fig.1. X-ray film viewer with shutters for mammograms NGP 21 mZ

- 1. Power connection unit
- 2. Illuminance adjustment knob
- 3. Left vertical shutter repositioning handle
- 4. Right vertical shutter repositioning handle
- 5. Lower horizotal shutter repositioning handle
- 6. Upper horizontal shutter repositioning hadle
- 7. Lines supporting the film