




Ultra-Viol sp.j. Pietras, Purgał, Wójcik 34 Stępowizna Str., 95-100 Zgierz, Poland VAT PL 727 00 21 903 www.ultraviol.pl/en Contact: phone number +48 42 717 77 45 ext. 21 mobile +48 725 779 277 fax +48 42 715 02 16, e-mail: office@ultraviol.pl

**TECHNICAL DATA SHEET** 

## NGP mZ/mzU



### NGP 31 mZ

#### X-RAY FILM VIEWER WITH SHUTTERS FOR MAMMOGRAMS

#### HOW DOES THE X-RAY FILM VIEWER FOR MAMMOGRAMS WORK?

NGP mZ/mZU X-ray film viewers with shutters are medical devices designed for the analysis of medical mammography images on X-ray films, which is one of the basic methods of diagnosing human diseases. The devices are characterized by high luminous flux density, flicker-free, energy-saving high-frequency light for film reading without eyestrain. The devices do not come into contact with patients as they are devices supporting the process of analyzing X-rays by a doctor. The products are made in the 1st class of protection against electric shock. They can be used in operating theaters, doctor's offices, X-ray laboratories, etc.



Shutter repositioning handle

### **BASIC DATA:**

Mounting type	wall-mounted (on special hooks)
Casing material (viewer housing)	powder-coated steel sheet
Viewer screen material	PMMA
Switch on/off	built-in x-ray film viewer body (Fig. 1 point 1)
X-ray viewer supplied with a magnifying glass	yes
Mobile cental film holder	no
Ambient temperature	+10°C to +40°C
Relative humidity	30% to 70%
Atmospheric pressure	700 hPa to 1060 hPa
Declaration of conformity	yes
User's manual English version	yes

EDITION: 11/2024





#### **TECHNICAL DATA SHEET**

# NGP mZ/mzU

## NGP 31 mZ

#### X-RAY FILM VIEWER WITH SHUTTERS FOR MAMMOGRAMS

#### **TECHNICAL DATA:**

IECHNICAL DATA:	
Supply voltage	230 V, 50 Hz
Power consumption	175 W +/- 10 %
Luminance	6800 cd/m <sup>2</sup> +/- 10 %
Step-less luminance adjustment	10 - 100 %
Colour temperature of the light of the lamps	≈ 6500°K (daylight)
Shutters for glare-free reading of radiographs	yes
Screen dimensions (L x H)	96 x 30 cm ( 2 fields)
Overall dimensions (L x W x H)	1240 x 120 x 940 mm
Total mass	57.0 kg
Class of protection against electric shock	1
Ingress Protection Code	IP 20
Class for the medical environment	B - home
Group according to PN-EN 55011 Clause 5	1
Power cord length	2.5 m, ended with the socket plug




Fig. 1 X-ray film viewer with shutters for mammograms NGP 31 mZ  $\,$ 

- 1. Power connection unit
- 2. Illuminance adjustment knob
- 3. Left vertical shutter repositioning handle
- 4. Right vertical shutter repositioning handle
- 5. Lower horizotal shutter repositioning handle
- 6. Upper horizontal shutter repositioning hadle